

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

Material number DRUCKLUFTSPRAY_BRENNBAR

Version: 12.0
Replaces version: 11.1

Revision date: 18/1/2023
Date of print: 7/12/2023

Page: 1 of 9
Language: en-IE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

This safety data sheet pertains to the following products:
WIKO®COMPRESSED AIR SPRAY FLAMMABLE

UFI: 3FA0-20VX-7007-S8WA

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Compressed air spray flammable 400ml

1.3 Details of the supplier of the safety data sheet

Company name: WIKO Klebetechnik Sp. z o.o.
Street/POB-No.: ul. Ekonomiczna 8
Postal Code, city: PL-42-271 Czestochowa
WWW: www.gluetec-group.com
E-mail: info.pl@gluetec-group.com
Telephone: +48 (0) 34 372 58 58
Telefax: +48 (0) 34 371 11 14

Department responsible for information:
Telephone: +48 (0) 34 372 58 58, E-mail: info.pl@gluetec-group.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen, Germany,
Telephone: +49 551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2 Label elements

Labelling (CLP)



Signal word: **Danger**

Hazard statements: H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Precautionary statements: P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

Material number DRUCKLUFTSPRAY_BRENNBAR

Version: 12.0
Replaces version: 11.1

Revision date: 18/1/2023
Date of print: 7/12/2023

Page: 2 of 9
Language: en-IE

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

health hazards: Contact with the product can cause cold burns or frostbite.

Endocrine disrupting properties, Results of PBT and vPvB assessment:
No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Mixture of the substances listed below with non-hazardous additions:

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119485395-27-xxxx EC No. 200-857-2 CAS 75-28-5	Isobutane Flam. Gas 1; H220. Press. Gas (Comp.); H280.	50 - 100 %
REACH 01-2119486944-21-xxxx EC No. 200-827-9 CAS 74-98-6	Propane Flam. Gas 1; H220. Press. Gas (Comp.); H280.	25 - 50 %

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection!
In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical aid in case of troubles.
Following skin contact: Wash with generous amount of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.
After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
After swallowing: Do not induce vomiting. Rinse mouth and seek medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Water spray jet, alcohol resistant foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:
Full water jet

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

Material number DRUCKLUFTSPRAY_BRENNBAR

Version: 12.0
Replaces version: 11.1

Revision date: 18/1/2023
Date of print: 7/12/2023

Page: 3 of 9
Language: en-IE

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Vapours form potentially explosive mixtures with air. Heavier than air, they proceed at floor level and may backflash over great distances when ignited.

May form dangerous gases and vapours in case of fire. Furthermore, there may develop: Carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and fire fighter's clothing conforming to European standard EN 469. Do not breathe fumes.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion.
Cool endangered containers with water spray and, if possible, remove from danger zone.
In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Do not allow fire water to penetrate into surface or ground water.
Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe spray. Avoid contact with the substance.
In case of leakage, eliminate all ignition sources. Provide adequate ventilation.
Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away.
Cordon off downwind area at risk and warn inhabitants.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains.
If necessary notify appropriate authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Thoroughly clean surrounding area.
In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).
Never return spills in original containers for re-use.
Use explosion-proof equipment and non-sparking tools/utensils.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Do not breathe spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.
When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
Use only non-sparking tools.
Take precautionary measures against static discharges.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

Material number DRUCKLUFTSPRAY_BRENNBAR

Version: 12.0
Replaces version: 11.1

Revision date: 18/1/2023
Date of print: 7/12/2023

Page: 4 of 9
Language: en-IE

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store containers in upright position.

Hints on joint storage:

Do not store together with strong oxidizing agents or peroxides.
Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
75-28-5	Isobutane	Ireland: 15 minutes	1000 ppm

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Personal protection equipment

Occupational exposure controls

Respiratory protection:

Respiratory protection must be worn whenever the WEL levels have been exceeded.
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

Hand protection:

Protective gloves according to BS EN 374.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection:

Tightly sealed goggles according to BS EN ISO 16321-1:2022.

Body protection:

Flame retardant, antistatic and chemical resistant protective clothing.

General protection and hygiene measures:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
Do not breathe spray. Do not get in eyes, on skin, or on clothing.
When using do not eat or drink. Contaminated work clothing should not be allowed out of the workplace.
Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.
When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa

liquid
Form: Aerosol
colourless

Colour:

Odour:

characteristic

Odour threshold:

Not determined

Melting point/freezing point:

Not determined

Initial boiling point and boiling range:

-21 °C

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

Material number DRUCKLUFTSPRAY_BRENNBAR

Version: 12.0
Replaces version: 11.1

Revision date: 18/1/2023
Date of print: 7/12/2023

Page: 5 of 9
Language: en-IE

Flammability:	Extremely flammable aerosol. approx. 365 °C
Upper/lower flammability or explosive limits:	LEL (Lower Explosion Limit): 1.50 Vol-% (propellant) UEL (Upper Explosive Limit): 10.90 Vol-% (propellant)
Flash point/flash point range:	approx. -80 °C
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	Not determined
pH:	Not determined
Viscosity, dynamic:	Not determined
Viscosity, kinematic:	Not determined
Water solubility:	at 25 °C: < 0.1 g/L
Partition coefficient: n-octanol/water:	No data available
Vapour pressure:	at 20 °C: 1200 - 7500 hPa
Density:	at 20 °C: 0.548 g/cm ³
Vapour density:	Not determined
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	Product is not explosive. Potentially explosive vapour/air mixtures may form.
Oxidizing characteristics:	not oxidising
Auto-ignition temperature:	Not determined
Evaporation rate:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Pressurised container: May burst if heated.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

Strong oxidizing agents, peroxides.

10.6 Hazardous decomposition products

Thermal decomposition:	No decomposition when used properly. Not determined
------------------------	--

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

Material number DRUCKLUFTSPRAY_BRENNBAR

Version: 12.0
Replaces version: 11.1

Revision date: 18/1/2023
Date of print: 7/12/2023

Page: 6 of 9
Language: en-IE

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects:

- Acute toxicity (oral): Lack of data.
- Acute toxicity (dermal): Lack of data.
- Acute toxicity (inhalative): Lack of data.
- Skin corrosion/irritation: Lack of data.
- Serious eye damage/irritation: Lack of data.
- Sensitisation to the respiratory tract: Lack of data.
- Skin sensitisation: Lack of data.
- Germ cell mutagenicity/Genotoxicity: Lack of data.
- Carcinogenicity: Lack of data.
- Reproductive toxicity: Lack of data.
- Effects on or via lactation: Lack of data.
- Specific target organ toxicity (single exposure): Lack of data.
- Specific target organ toxicity (repeated exposure): Lack of data.
- Aspiration hazard: Lack of data.

11.2 Information on other hazards

Endocrine disrupting properties: No data available

Symptoms

Vapours in high concentrations have anaesthetic effect.
In case of inhalation:
Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect.
Other symptoms: Headache, dizziness, nausea, drowsiness, Shortage of breath, Cough.
In case of ingestion: May cause nausea, vomiting and diarrhoea.
Ingestion may produce abdominal pain, irritant of lips, mouth tongue and pharynx.
After contact with skin: Can cause frostbite.
After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.
Can cause frostbite.

SECTION 12: Ecological information

12.1 Toxicity

Further details: No data available

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

Material number DRUCKLUFTSPRAY_BRENNBAR

Version: 12.0
Replaces version: 11.1

Revision date: 18/1/2023
Date of print: 7/12/2023

Page: 7 of 9
Language: en-IE

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

AOX reference: Product does not contain organically bound halogen (AOX).
General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 05 04* = Gases in pressure containers (including halons) containing hazardous substances
* = Evidence for disposal must be provided.

Recommendation: Special waste. Do not open with force or incinerate, even when empty.
Dispose of waste according to applicable legislation.
Do not dispose of with household waste.

Package

Waste key number: 15 01 11* = metallic packaging containing a hazardous solid porous matrix (for example asbestos),
including empty pressure containers
* = Evidence for disposal must be provided.

Recommendation: Empty carefully and completely, if possible.
Dispose of waste according to applicable legislation.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID, IMDG, IATA-DGR: UN 1950

14.2 UN proper shipping name

ADR/RID, IMDG: UN 1950, AEROSOLS
IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID: Class 2, Code: 5F
IMDG: Class 2, Subrisk -, see SP63
IATA-DGR: Class 2.1

14.4 Packing group

ADR/RID, IATA-DGR: not applicable
IMDG: -

14.5 Environmental hazards

Dangerous for the environment: Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant: no



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

Material number DRUCKLUFTSPRAY_BRENNBAR

Version: 12.0
Replaces version: 11.1

Revision date: 18/1/2023
Date of print: 7/12/2023

Page: 8 of 9
Language: en-IE

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: RID: Kemmler-number 23, UN number UN 1950
Hazard label: 2.1
Special Provisions: 190 327 344 625
Limited quantities: 1 L
EQ: E0
Package - Instructions: P207 LP200
Package - Special Provisions: PP87 RR6 L2
Special provisions for packing together: MP9
Tunnel restriction code: D

Sea transport (IMDG)

EmS: F-D, S-U
Special Provisions: 63 190 277 327 344 381 959
Limited quantities: See SP277
Excepted quantities: E0
Package - Instructions: P207, LP200
Package - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - EC member states

Volatile organic compounds (VOC):

100 % by weight = 550 g/L

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances
[Seveso-III-Directive]

Physical hazards: Code P3a, Quantity threshold 150 000 kg / 500 000 kg

Use restriction according to REACH annex XVII, no.: 3, 40

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



WIKO®DRUCKLUFTSPRAY BRENNBAR/COMPRESSED AIR SPRAY FLAMMABLE

Material number DRUCKLUFTSPRAY_BRENNBAR

Version: 12.0
Replaces version: 11.1

Revision date: 18/1/2023
Date of print: 7/12/2023

Page: 9 of 9
Language: en-IE

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H220 = Extremely flammable gas.
H222 = Extremely flammable aerosol.
H229 = Pressurised container: May burst if heated.
H280 = Contains gas under pressure; may explode if heated.

Reason of change:

Material number
Changes in section 1: Product identifier (Trade name), Changes of product list
23/5/2013

Date of first version:

Department issuing data sheet:

see section 1: Department responsible for information

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
Aerosol: Aerosol
AOX: Adsorbable Organic Halogens
AS/NZS: Australian Standards/New Zealand Standards
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EN: European Standard
EQ: Excepted quantities
EU: European Union
Flam. Gas: Flammable gases
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
Press. Gas: Gases under pressure
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Most recent product information is available at:
<http://sumdat.net/pd4ersnv>

