

## AEROSOLS



## Surface protection and preparation **WIKO® WELDING SPRAY**

WIKO® WELDING SPRAY serves to protect and keep clean from spraying without affecting the weld. The forming protective film prevents the adhesion of welding spatters.

Welding beads remain loose on the surface and can be easily wiped off.

- Tough protection during welding process
- prevents the sticking of welding spatters
- Increases the durability of gas tips and contact tips

## Application areas

- Electro-welding and inert gas shielded arc welding
- Cleaning and maintenance of welding nozzles
- Protection of components/work pieces to be welded

## Sizes / article number

400 ml can

ASWS.D400

## Application

Clean the designated areas of dirt, rust, oil and grease before the application (we recommend the usage of a suitable WIKO® cleaner, e.g. WIKO® INDUSTRIAL QUICK CLEANER art. No. AISR.D400). Shake the aerosol can intensively for approx. 2 minutes and perform a test spraying. Apply the product crosswise from a distance of 20 to 30 cm and cover the whole area. In order to protect the surface of work pieces, spray each side of the weld within a range of 10 cm.

## Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

# TECHNICAL DATA SHEET



## Safety data sheets

Please refer to the current data sheet for safety relevant data.  
Click or scan here:



### Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.